

USB to Quad RS422



USB to Quad RS422

ROTRONICS SYSTEMS LTD
UNIT 5
RIVERSIDE PARK
FARNHAM
SURREY
GU9 7UG
UK

E: bob@rotronics.co.uk

T: +44(0)1252 722686 www.rotronics.co.uk



E&OE

VI 02-09-2016

FEATURES

- Four independent RS422 ports on RJ45
- Diagnostic Tx and Rx Leds per port
- Galvanic opto isolation rated to 1.5kV
- Metal Case. Width 95mm, height 25mm, depth 63mm
- 2x M3 front mounting screws
- Optional 1U mounting plate holds four Quad adaptors (16 ports total as picture).
- Powered from USB.
- Electronics uses the reliable FTDI FT4232H device to provide up to 8 Mbps.
- Royalty free drivers for Windows, Mac and Linux.
- Operating range -40C to +85C
- RoHS and CE and FCC compliant
- Clear documentation supplied (and online)
- Drivers supplied (and online)
- Expert support at Rotronics.

PROFESSIONAL DESIGN

- Rotronics designed this for their own requirements of high stability and reliability.
- Galvanic isolation resists static destruction.
- Diagnostic LEDs improve hardware fault finding.
- M3 mounting screw holes